



Moisture Analyzer Portfolio

Overview of Standard Analyzers



Model	MA35	MA37	MA160
Features	<ul style="list-style-type: none"> k Rugged entry-level model k Easy operation k For repetitive measurements 	<ul style="list-style-type: none"> k Faster analysis (due to more powerful heating unit than that in the MA35) k Touch screen k Easy to clean k Direct data transfer k Function testing 	<ul style="list-style-type: none"> k AURI metal tube heater for the highest measurement speeds k Touch screen k Password protection k Memory for methods k Method Development Assistant k Memory for results k Easy to clean k Direct data transfer k Function testing
Moisture measurement range in %	> 1	> 1	> 1
Typical uses	<ul style="list-style-type: none"> k Moisture analysis of recurrent samples 	<ul style="list-style-type: none"> k Moisture analysis of recurrent samples 	<ul style="list-style-type: none"> k Moisture analysis of recurrent samples k Moisture analysis of the widest variety of samples
Typical industrial sectors	<ul style="list-style-type: none"> k Sewage treatment plants k Biogas facilities k Manufacturing k Paints, lacquers, varnishes, dyes 	<ul style="list-style-type: none"> k Food and beverage (incoming quality control) k Building materials and wood industries k Animal feed 	<ul style="list-style-type: none"> k Chemical analytical labs k QA QM k Food & beverage k Manufacturing k Research and development

Overview of Premium Analyzers



Model	MA100	LMA100	LMA200
Features	<ul style="list-style-type: none"> k Analytical weighing system (0.1 mg) k Different, interchangeable heat sources k Memory for methods k Easy operation k Password protection k Various heating programs k Various shutoff criteria k The most flexible range of applications k Statistics function 	<ul style="list-style-type: none"> k Analytical weighing system (0.1 mg) k Modular design consisting of operating and heating units (up to 4) k User management k Memory for methods k Large sample chamber k Special weighing pan for plastic samples k Syringe and concentration modes k Statistics function and memory for results 	<ul style="list-style-type: none"> k Analytical weighing system (0.1 mg) k User management k Microwave drying k The fastest measurements (many take less than 1 – 2 min.) k Carousel-type sample holder k Memory for methods k Statistics function and memory for results
Moisture measurement range in %	>0.01	>0.01	>8
Typical uses	<ul style="list-style-type: none"> k Analysis of samples with a low moisture content (below 1%), such as plastic k Moisture analysis of the widest variety of samples 	<ul style="list-style-type: none"> k Analysis of samples with a low moisture content (below 1%), such as plastic k Special applications (e.g., highly volatile substances) 	<ul style="list-style-type: none"> k Analysis of samples with a high moisture content (liquids, pastes, etc.)
Typical industrial sectors	<ul style="list-style-type: none"> k Processing of plastics k Pharma (granules and powder) k Food and beverage k R&D k Paper and textile industries 	<ul style="list-style-type: none"> k Processing of plastics k Pharma (granules and powder) k Food and beverage k Chemical industry k Automotive industry 	<ul style="list-style-type: none"> k Food and beverage (dairies) k Pharma (extracts, homeopathic products) k Water-based paints and other coatings k Cosmetics industry

Germany
 Sartorius Lab Instruments
 GmbH & Co. KG
 Otto-Brenner-Strasse 20
 37079 Goettingen
 Phone +49.551.308.0
 Fax +49.551.308.3289
www.sartorius.com

Specifications subject to change without notice.
 Copyright Sartorius Lab Instruments GmbH & Co. KG.
 Printed in the EU on paper bleached without chlorine.
 Publication No.: W--1521-e170602
 Order No.: 98649-020-30
 Ver. 06 | 2017